

Flexible Waterproof Building Board for Curved Applications

Key Features

- 100% waterproof and vapour resistant.
- Can form curves as tight as 200 mm radius.
- Can be tiled or rendered on both sides.
- Unique honeycomb surface, which increases adhesion.
- Suitable for internal and external use.



Available Sizes

Orientation	Dimensions (mm)	Thickness (mm)
Longitudinal	600 × 2500	20
Transverse	600 × 1250	30

Flexible Waterproof Building Board for Curved Applications

Installation Instructions

- Curved Multiboards come flat packed and can be easily bent to the required radius.
- Ideally the best way to bend the curved Multiboard is to always have the slits on the inside of the circular shape and the smooth edge on the outside.
- Fix to either a curved masonry surface with a continuous bed of flexible tile adhesive or to a wooden or metal frame.
- Place studs at 200 mm centres maximum. Screw curved board at 300mm vertically and 200mm horizontally.
- Tape joints with Marmox Reinforcing Tape.
- Tiling can now begin.
- For external use it is recommended to use a thin layer of plywood behind the sheet.



Note: If the boards are curved outward, then a flexible cement-based tile adhesive needs to be used to fill out all of the slits on the surface and a sheet of Marmox fibreglass mesh needs to be laid over.